

AMENDMENTS

In the Claims

Please delete Claims 19-20 and 31 without prejudice:

1. – 9. (canceled)

10. (previously presented) A method for secure communication between a client and a server in a data processing system, the method comprising:

generating a client message at the client;

retrieving an embedded server public key from a read-only memory structure in an article

5 of manufacture in the client, the read-only memory structure having an embedded client private key, the embedded server public key and the embedded client private key not being related by a public/private key pair relationship, the embedded client private key being associated with a client public key generated and stored exclusively outside the client;

10 encrypting the client message with the embedded server public key;

sending the client message to the server;

receiving a server message including application code from the server at the client in

response to the client message, the application code having a first portion

encrypted with a server private key and a second portion, wherein the first portion

15 of the application code is small relative to the second portion of the application code;

authenticating the first portion of the application code with the embedded server public key; and

authenticating the second portion of the application code using an integrity checking

20 algorithm that is not a public key algorithm.

11. (previously presented) The method of claim 10 further comprising:
retrieving client authentication data;
retrieving an embedded client private key from a read-only memory structure in an article
of manufacture in the client;
5 encrypting the client authentication data with the embedded client private key; and
storing the encrypted client authentication data in the client message.

12. (original) The method of claim 11 further comprising:
retrieving an embedded client serial number from a read-only memory structure in an
article of manufacture in the client; and
storing a copy of the embedded client serial number in the client message.

13. – 24. (canceled)

25. (previously presented) A method for secure communication between a client and a server in a data processing system, the method comprising:

receiving a client message from the client;

retrieving a server private key;

5 decrypting the client message with the server private key;

retrieving a client serial number from the decrypted client message;

retrieving a client public key that is associatively stored with the retrieved client serial

number, wherein the client public key corresponds to an embedded client private

key in a read-only memory structure in an article of manufacture in the client and

10 is generated and stored exclusively outside the client; and

generating a server message including application code at the server in response to the

client message, the application code having a first portion encrypted with the

server private key and a second portion, the first portion being authenticable with

a server public key and the second portion being authenticable with an integrity

15 checking algorithm that is not a public key algorithm, wherein the first portion of the application code is small relative to the second portion of the application code;

wherein the read-only memory structure has an embedded server public key, the

embedded server public key and the embedded client private key not being related

by a public/private key pair relationship.

26. (original) The method of claim 25 further comprising:

retrieving encrypted client authentication data from the client message;

decrypting the client authentication data with the retrieved client public key; and

verifying the decrypted client authentication data.

27. – 39. (canceled)